


CABLE HOLDERS



Cast bronze or aluminum clamp for use in supporting cable on metal column or rib – may be used on column edge to 1/2" thick – compression type cable holder for main sized cable through No. 605 – with one 1/4" bolt for tension on column or rib. Rubber caps included on bolts to prevent damage to roof. Recommended torque on mounting bolt: 15 in./lbs. maximum. Overall dimensions - 1-1/4" x 1-1/4" x 1-1/2".




Cat. No. 77X – Copper - 2.1 oz.

Cat. No. A77X – Aluminum - 0.6 oz.


STANDING SEAM CABLE HOLDERS

Cast bronze or aluminum cable holder for use on standing seams, steel beams, etc., where no penetration of metal is desired or permitted. Consists of No. 77X or No. A77X clamp with No. 72 or No. A72 loop, two 1/4" stainless bolts. Rubber caps included on bolts to prevent damage to roof. Recommended torque on mounting bolt: 15 in./lbs. maximum. For main and secondary cables and wires. Overall dimensions - 1-1/4" x 1-1/4" x 2".



Cat. No. 75 – Copper - 2.6 oz.



Cat. No. A75 – Aluminum - 1 oz.



Machined brass or aluminum hexagonal holder for use on standing seams, steel beams, etc. where no penetration of metal is desired or permitted. Comes with No. 72 or No. A72 loop, which can be attached to 1/4" stainless bolt, 1/4" stainless nut for tightening loop. Rubber cap included on bolts to prevent damage to roof. For main and secondary cables and wires.

Cat. No. 79 – Copper - 2.2 oz.

Cat. No. A79 – Aluminum - 1 oz.



ROBBINS LIGHTNING, INC.

124 EAST SECOND STREET PHONE (660) 582-3156 FAX (660) 582-3039 P.O. BOX 440 MARYVILLE, MISSOURI 64468-0440

