

# ALUMINUM CONDUCTORS (For Secondary Bonding Use)

ALL ITEMS



**Cat. No. A10** – 14 strands of 14 gauge aluminum wire in smooth weave configuration, 5/16" diameter, 57,000 circular mil cross section, (exceeds #4 AWG). Weight of aluminum – 58 pounds per 1,000'.




**Cat. No. A11** – 22 strands of 14 gauge aluminum wire in smooth weave configuration, 7/16" diameter, 90,000 circular mil cross section, (exceeds #2 AWG). Weight of aluminum – 90 pounds per 1,000'.

**Cat. No. A11A** – 11 strands of 14 gauge aluminum wire in smooth weave configuration, 1/4" diameter, 45,000 circular mil cross section, (#4 AWG). Weight of aluminum – 47 pounds per 1,000'.

All Secondary Conductors available in 25',  
50', 100' or 500' coils or spools.

**Cat. No. A11C** – Aluminum #4 AWG bare wire, soft drawn, 41,500 circular mil cross section. Weight of aluminum – 40 pounds per 1,000'.

**Cat. No. A11D** – Aluminum #2 AWG bare wire, soft drawn, 66,400 circular mil cross section. Weight of aluminum – 60 pounds per 1,000'.



# ROBBINS LIGHTNING, INC.

124 EAST SECOND STREET PHONE (660) 582-3156 FAX (660) 582-3039 P.O. BOX 440 MARYVILLE, MISSOURI 64468-0440