
(For Main Conductor Use)





Cat. No. 12 – Solid copper rod, 1/2" diameter, hard drawn. May be substituted for stranded cable where needed to prevent mechanical damage or to bridge open spaces. Weight – 761 pounds per 1,000'.

← Class II


Available in lengths 144'' or shorter – each end threaded 1/2'' - 13 NC for coupling.

Class I →


Cat. No. 13 – Solid copper rod, 3/8" diameter, hard drawn. May be substituted for stranded cable where needed to prevent mechanical damage or to bridge open spaces. Weight – 428 pounds per 1,000'.

Available in lengths 144'' or shorter – each end threaded 3/8'' - 16 NC for coupling. 3/8'' = 12' Lengths

1/2'' = 7' Lengths



ALUMINUM ROD CONDUCTORS (For Main Conductor Use)



Cat. No. A12 — Solid aluminum rod, 1/2" diameter, hard drawn. May be substituted for stranded cable where needed to prevent mechanical damage or to bridge open spaces. Weight — 240 pounds per 1,000'.

← Class I

Available in lengths 84'' or shorter – each end threaded 1/2'' - 13 NC for coupling.

Class II —

Cat. No. A13 — Solid aluminum rod, 5/8" diameter, hard drawn. May be substituted for stranded cable where needed to prevent mechanical damage or to bridge open spaces. Weight — 135 pounds per 1,000'.

Available in lengths 144'' or shorter – each end threaded 3/8'' - 16 NC for coupling.

