
CABLE SPLICERS



COMBINATION SPLICERS


Heavy cast bronze or aluminum splicer for main cable through No. 605 to secondary wire or cable through 1/4'' diameter -4'' long - two bolt tension on cable. Overall dimensions -4'' x 1-1/4''.

Cat. No. 53 – Copper - 10.6 oz. Cat. No. A53 – Aluminum Class I - 3.7 oz. Cat. No. A53AL – Aluminum Class II - 4.2 oz.



Heavy cast bronze or aluminum splicer for main cable through No. 605 to secondary wire or cable through 1/4'' diameter -2'' long - one bolt tension on cable. Overall dimensions $-2'' \times 1-1/4''$.

Cat. No. 53A – Copper - 5.3 oz. Cat. No. A53A – Aluminum Class I - 1.8 oz. Cat. No. A53ALH – Aluminum Class II - 1.8 oz.



SECONDARY WIRE SPLICERS

Heavy cast bronze or aluminum splicer for secondary wires and miniature cables through 1/4'' diameter -4'' long -t wo bolt tension on cable. Overall dimensions $-4'' \ge 1-1/4''$.

Cat. No. 58 – Copper - 7.7 oz. **Cat. No. A58** – Aluminum - 2.9 oz. Heavy cast bronze or aluminum splicer for secondary wires and miniature cables through 1/4'' diameter -2'' long – one bolt tension on cable. Overall dimensions $-2'' \times 1-1/4''$.

Cat. No. 58A – Copper - 3.8 oz. **Cat. No. A58A** – Aluminum - 1.4 oz.





