

GROUND RODS

ALL ITEMS



UL 467
UL 96

COPPERCLAD - STANDARD

Our copperclad ground rods meet standards UL 467, ANSI C33.8 RUS, and are approved for use in lightning protection per UL 96 and UL 96A. Copper cladding is a minimum of 0.010 inches thick.

- Cat. No. 90-8 – 1/2" diam. x 8' long - 5 lbs. - 8 oz.
- Cat. No. 91-10 – 1/2" diam. x 10' long - 7 lbs.
- Cat. No. 94-8 – 5/8" diam. x 8' long - 7 lbs.
- Cat. No. 94-10 – 5/8" diam. x 10' long - 9 lbs.
- Cat. No. 97-8 – 3/4" diam. x 8' long - 10 lbs.
- Cat. No. 97-10 – 3/4" diam. x 10' long - 13 lbs.
- Cat. No. 97-12 – 3/4" diam. x 12' long - 15 lbs.
- Cat. No. 97C-10 – 1" diam. x 10' long - 18 lbs.

COPPERCLAD - SECTIONAL

(Threaded both ends)

- Cat. No. 90-8S – 1/2" diam. x 8' long - 5 lbs. - 8 oz.
- Cat. No. 91-10S – 1/2" diam. x 10' long - 7 lbs.
- Cat. No. 94-8S – 5/8" diam. x 8' long - 7 lbs.
- Cat. No. 94-10S – 5/8" diam. x 10' long - 9 lbs.
- Cat. No. 97-8S – 3/4" diam. x 8' long - 10 lbs.
- Cat. No. 97-10S – 3/4" diam. x 10' long - 13 lbs.
- Cat. No. 97C-10S – 1" diam. x 10' long - 18 lbs.

SOLID COPPER

- Cat. No. 90-8-C – 1/2" diam. x 8' long - 6 lbs. - 6 oz.
- Cat. No. 91-10-C – 1/2" diam. x 10' long - 8 lbs.
- Cat. No. 94-8-C – 5/8" diam. x 8' long - 10 lbs.
- Cat. No. 94-10-C – 5/8" diam. x 10' long - 12 lbs. - 8 oz.
- Cat. No. 97-8-C – 3/4" diam. x 8' long - 14 lbs. - 6 oz.
- Cat. No. 97-10-C – 3/4" diam. x 10' long - 18 lbs.
- Cat. No. 97C-10-C – 1" diam. x 10' long - 32 lbs.

STAINLESS STEEL

- Cat. No. 90-8ST – 1/2" diam. x 8' long - 5 lbs. - 11 oz.
- Cat. No. 91-10ST – 1/2" diam. x 10' long - 7 lbs. - 2 oz.
- Cat. No. 94-8ST – 5/8" diam. x 8' long - 9 lbs.
- Cat. No. 94-10ST – 5/8" diam. x 10' long - 11 lbs.
- Cat. No. 97-8ST – 3/4" diam. x 8' long - 12 lbs. - 13 oz.
- Cat. No. 97-10ST – 3/4" diam. x 10' long - 16 lbs.
- Cat. No. 97C-8ST – 1" diam. x 8' long - 22 lbs. - 11 oz.
- Cat. No. 97C-10ST – 1" diam. x 10' long - 27 lbs.

ROBBINS LIGHTNING, INC.

124 EAST SECOND STREET PHONE (660) 582-3156 FAX (660) 582-3039 P.O. BOX 440 MARYVILLE, MISSOURI 64468-0440

-121-

