

GROUND ROD COUPLINGS



Coupling

Made of strong copper alloy.


Cat. No. 203-G2 – for 1/2" Ground Rod - 2.2 oz.

Cat. No. 203-G5 – for 5/8" Ground Rod - 3.8 oz.

Cat. No. 203-G6 – for 3/4" Ground Rod - 4.8 oz.

Cat. No. 203-G8 – for 1" Ground Rod - 13.3 oz.

GROUND ROD DRIVING STUD



Driving Stud

For use with couplings to protect threads.
Made of high strength steel.

Cat. No. 232-G2 – for 1/2" Coupling - 1.8 oz.

Cat. No. 232-G5 – for 5/8" Coupling - 3 oz.

Cat. No. 232-G6 – for 3/4" Coupling - 5.3 oz.

Cat. No. 232-G8 – for 1" Coupling - 9.8 oz.

GROUND ROD DRIVING SLEEVE

For use on standard ground rods to prevent
top from mushrooming.
Made of high strength steel.

Cat. No. 233-G2 – for 1/2" Ground Rod - 1lb. - 11 oz.

Cat. No. 233-G5 – for 5/8" Ground Rod - 1lb. - 11 oz.

Cat. No. 233-G6 – for 3/4" Ground Rod - 1lb. - 9 oz.



Driving Sleeve

ROBBINS LIGHTNING, INC.

124 EAST SECOND STREET PHONE (660) 582-3156 FAX (660) 582-3039 P.O. BOX 440 MARYVILLE, MISSOURI 64468-0440

