


MOLDS FOR LIGHTNING PROTECTION CABLE

| | CADWELD® TYPE GY |  | | THERMOWELD® TYPE CR-3 | |
|-----------------|------------------------|---|----------------------------|-----------------------------|----|
| GRD ROD SIZE | CABLE CODE | CADWELD® MOLD NUMBER | THERMOWELD® MOLD NUMBER | CART. SIZE | PK |
| 3/4" ③ | E | GYE-188E | M-5121 | 150 | 24 |
| | F | GYE-188F | M-5123 | 150 | 24 |
| | G | GYE-188G | M-2415 | 200 | 24 |
| | H | GYE-188H | M-2416 | 200 | 24 |
| | J | GYE-188J | M-2417 | 200 | 24 |
| | K | GYE-188K | M-2418 | 200 | 24 |
| | L | GYE-188L | M-2419 | 250 | 24 |
| | Q | GYE-182Q | M-1596 | 150 | 24 |
| 1" ④ | A | GYE-228A | M-2421 | 90 | 24 |
| | B | GYE-228B | M-2422 | 115 | 24 |
| | C | GYE-228C | M-2423 | 150 | 24 |
| | D | GYE-228D | M-2424 | 150 | 24 |
| | E | GYE-228E | M-2174 | 150 | 24 |
| | F | GYE-228F | M-2425 | 150 | 24 |
| | G | GYE-228G | M-2426 | 200 | 24 |
| | H | GYE-228H | M-5122 | 200 | 24 |
| | J | GYE-228J | M-5132 | 200 | 24 |
| | K | GYE-228K | M-2427 | 200 | 24 |
| | L | GYE-228L | M-2428 | 250 | 24 |
| | Q | GYE-222Q | M-1605 | 150 | 24 |

NOTES

1. .505" actual diameter. THERMOMOLDS for 1/2" ground rod fits both copper-clad ground rods and stainless steel ground rods.
2. .563" actual diameter. For full 5/8" (.625) ground rod and roll-threaded rod, add suffix "-N" to mold number, i.e. M-5058-N is full 5/8" diameter ground rod or roll-threaded rod to 4/0 lightning protection cable.
3. .682" actual diameter. For full 3/4" (.750) ground rod and roll-threaded rod, add suffix "-N" to mold number, i.e. M-2420-N is full 3/4" diameter ground rod or roll-threaded rod to 4/0 lightning protection cable.
4. .914" actual diameter. For full 1" (1.00) ground rod and roll-threaded rod, add suffix "-N" to mold number, i.e. M-2429-N is full 1" diameter ground rod or roll-threaded rod to 4/0 lightning protection cable.