

ALL THREAD ROD AND POINT EXTENSION ROD

ALL ITEMS



ALL THREAD ROD

All thread rod with standard N.C. threads. Available in lengths up to 144". Standard sizes 12", 18", 24", 36".

Copper

Cat. No. 220 – 3/8" dia. 0.57 oz./in.

Cat. No. 221 – 1/2" dia. 1 oz./in.

Cat. No. 222 – 5/8" dia. 1.6 oz./in.

Aluminum

Cat. No. A221 – 1/2" dia. 0.3 oz./in.

Cat. No. A222 – 5/8" dia. 0.48 oz./in.

Stainless Steel

Cat. No. 220SS – 3/8" dia. 0.5 oz./in.

Cat. No. 221SS – 1/2" dia. 0.89 oz./in.



POINT EXTENSION ROD

Solid copper or aluminum rod for extending length of points – standard N.C. thread both ends – available in lengths to 144". May also be substituted for stranded cable to prevent mechanical damage or to bridge open spaces.

Specify exact length required, such as Cat. No. 212 (1/2" x 48").

Copper

Cat. No. 212 – 1/2" dia. 1 oz./in.

Cat. No. 213 – 3/8" dia. 0.57 oz./in.

Cat. No. 214 – 5/8" dia. 1.6 oz./in.

Aluminum

Cat. No. A212 – 1/2" dia. 0.3 oz./in.

Cat. No. A214 – 5/8" dia. 0.48 oz./in.



SAFETY BALLS

Machined brass or aluminum safety tip, 1-1/2" diameter, with internal threads - to be used on copper or aluminum extension rods in place of standard sharp points where safety to workers or pedestrians is a concern.



Cat. No. 110F – Copper - 2.2 oz.

Cat. No. A110F – Aluminum - 0.8 oz.

Cat. No. 110 – Copper - 7.7 oz.

Cat. No. A110 – Aluminum - 2.4 oz.

NO. 110




Specify diameter of threads – 3/8", 1/2" or 5/8".

SAFETY SLEEVE WITH SET SCREW


Cat. No. 110C – Copper - 4 oz.

Cat. No. A110C – Aluminum - 1.5 oz.


NO. 110F



Typical use on midroof point



NO. 110C



ROBBINS LIGHTNING, INC.

124 EAST SECOND STREET PHONE (660) 582-3156 FAX (660) 582-3039 P.O. BOX 440 MARYVILLE, MISSOURI 64468-0440

