

COUPLINGS AND ADAPTERS FOR POINTS

ALL ITEMS



ROD COUPLINGS

Couplings made of brass or aluminum hex rod for extending point lengths and adapting points to various special purpose bases. Overall length 1-1/2".

Copper

- Cat. No. 203-2F2F – 1/2" Female to 1/2" Female 2.2 oz.
- Cat. No. 203-3F3F – 3/8" Female to 3/8" Female 2.9 oz.
- Cat. No. 203-2F3F – 1/2" Female to 3/8" Female 2.6 oz.
- Cat. No. 203-5F5F – 5/8" Female to 5/8" Female 1.8 oz.
- Cat. No. 203-2F5F – 1/2" Female to 5/8" Female 2.1 oz.

- Cat. No. 203-2F2M – 1/2" Female to 1/2" Male 2.1 oz.
- Cat. No. 203-3F3M – 3/8" Female to 3/8" Male 1.8 oz.
- Cat. No. 203-2F3M – 1/2" Female to 3/8" Male 2.1 oz.
- Cat. No. 203-3F2M – 3/8" Female to 1/2" Male 2.2 oz.
- Cat. No. 203-5F5M – 5/8" Female to 5/8" Male 2.4 oz.
- Cat. No. 203-2F5M – 1/2" Female to 5/8" Male 2.2 oz.
- Cat. No. 203-5F2M – 5/8" Female to 1/2" Male 2.2 oz.

- Cat. No. 203-2M2M – 1/2" Male to 1/2" Male 1.8 oz.
- Cat. No. 203-3M3M – 3/8" Male to 3/8" Male 1.2 oz.
- Cat. No. 203-2M3M – 1/2" Male to 3/8" Male 1.4 oz.
- Cat. No. 203-5M5M – 5/8" Male to 5/8" Male 2.2 oz.
- Cat. No. 203-2M5M – 1/2" Male to 5/8" Male 2.1 oz.

Aluminum

- Cat. No. A203-2F2F – 1/2" Female to 1/2" Female 0.8 oz.
- Cat. No. A203-5F5F – 5/8" Female to 5/8" Female 0.6 oz.
- Cat. No. A203-2F5F – 1/2" Female to 5/8" Female 0.6 oz.

- Cat. No. A203-2F2M – 1/2" Female to 1/2" Male 0.6 oz.
- Cat. No. A203-5F5M – 5/8" Female to 5/8" Male 0.8 oz.
- Cat. No. A203-2F5M – 1/2" Female to 5/8" Male 0.8 oz.
- Cat. No. A203-5F2M – 5/8" Female to 1/2" Male 0.6 oz.

- Cat. No. A203-2M2M – 1/2" Male to 1/2" Male 0.8 oz.
- Cat. No. A203-5M5M – 5/8" Male to 5/8" Male 1 oz.
- Cat. No. A203-2M5M – 1/2" Male to 5/8" Male 1 oz.



Male to Male



Female to Male



Female to Female

BASE CENTER SET

Machined brass or aluminum fittings for use on all strap type point bases or for adapting points to metal surface up to 1/8" thick. Nut drilled and tapped with 3/8", 1/2" or 5/8" NC thread – bolt has 1/2" or 5/8" NC thread.

NOTE: When ordering aluminum base center set, No. A143L stainless steel lockwasher should also be ordered for tightening.

Copper

- Cat. No. 803-2 – 1/2" nut - 1.4 oz.
- Cat. No. 803-3 – 3/8" nut - 1.6 oz.
- Cat. No. 803-5 – 5/8" nut - 1.4 oz.

- Cat. No. 804-2 – 1/2" bolt - 0.8 oz.
- Cat. No. 804-5 – 5/8" bolt - 0.7 oz.


Aluminum

- Cat. No. A803-2 – 1/2" nut - 0.4 oz.
- Cat. No. A803-5 – 5/8" nut - 0.4 oz.

- Cat. No. A804-2 – 1/2" bolt - 0.21 oz.
- Cat. No. A804-5 – 5/8" bolt - 0.15 oz.



Nut



Bolt

ROBBINS LIGHTNING, INC.

124 EAST SECOND STREET PHONE (660) 582-3156 FAX (660) 582-3039 P.O. BOX 440 MARYVILLE, MISSOURI 64468-0440

