

DOUBLE SWIVEL ADAPTERS

ALL ITEMS



Double swivel adapters for use with standard points and bases to alter direction of point – each end threaded or drilled and tapped for desired use. Overall dimensions - 3-1/4" long x 1" diameter.

HEAVY CAST SWIVEL

Copper

- Cat. No. 836-2F2F – 1/2" Female to 1/2" Female - 8.3 oz.
- Cat. No. 836-2F2M – 1/2" Female to 1/2" Male - 10.2 oz.
- Cat. No. 836-2F3F – 1/2" Female to 3/8" Female - 8.5 oz.
- Cat. No. 836-2M3F – 1/2" Male to 3/8" Female - 10.4 oz.
- Cat. No. 836-3F3F – 3/8" Female to 3/8" Female - 8.6 oz.
- Cat. No. 836-3F3M – 3/8" Female to 3/8" Male - 9.8 oz.
- Cat. No. 836-2F5F – 1/2" Female to 5/8" Female - 8.1 oz.
- Cat. No. 836-2M5F – 1/2" Male to 5/8" Female - 10.2 oz.
- Cat. No. 836-5F5F – 5/8" Female to 5/8" Female - 8 oz.
- Cat. No. 836-5F5M – 5/8" Female to 5/8" Male - 10 oz.

Aluminum

- Cat. No. A836-2F2F – 1/2" Female to 1/2" Female - 3 oz.
- Cat. No. A836-2F2M – 1/2" Female to 1/2" Male - 3.7 oz.
- Cat. No. A836-5F5F – 5/8" Female to 5/8" Female - 3 oz.
- Cat. No. A836-5F5M – 5/8" Female to 5/8" Male - 4 oz.
- Cat. No. A836-2F5F – 1/2" Female to 5/8" Female - 3 oz.
- Cat. No. A836-2M5F – 1/2" Male to 5/8" Female - 3.9 oz.


MACHINED SWIVEL MADE OF HEX BRASS OR ALUMINUM

Copper


- Cat. No. 837-2F2F – 1/2" Female to 1/2" Female - 5.4 oz.
- Cat. No. 837-2F2M – 1/2" Female to 1/2" Male - 5.3 oz.
- Cat. No. 837-2F3F – 1/2" Female to 3/8" Female - 5.4 oz.
- Cat. No. 837-2M3F – 1/2" Male to 3/8" Female - 5.6 oz.
- Cat. No. 837-3F3F – 3/8" Female to 3/8" Female - 5.8 oz.
- Cat. No. 837-3F3M – 3/8" Female to 3/8" Male - 5.3 oz.
- Cat. No. 837-2F5F – 1/2" Female to 5/8" Female 5 oz.
- Cat. No. 837-2M5F – 1/2" Male to 5/8" Female 5.3 oz.
- Cat. No. 837-5F5F – 5/8" Female to 5/8" Female 4.8 oz.
- Cat. No. 837-5F5M – 5/8" Female to 5/8" Male 5.6 oz.

Aluminum


- Cat. No. A837-2F2F – 1/2" Female to 1/2" Female - 2.1 oz.
- Cat. No. A837-2F2M – 1/2" Female to 1/2" Male - 2.1 oz.
- Cat. No. A837-2F5F – 1/2" Female to 5/8" Female - 2.1 oz.
- Cat. No. A837-2M5F – 1/2" Male to 5/8" Female - 1.8 oz.
- Cat. No. A837-5F5F – 5/8" Female to 5/8" Female - 2.2 oz.
- Cat. No. A837-5F5M – 5/8" Female to 5/8" Male - 2.1 oz.




Female to Female




Female to Male



Typical use on sloping surface point



Female to Female



Female to Male



ROBBINS LIGHTNING, INC.

124 EAST SECOND STREET PHONE (660) 582-3156 FAX (660) 582-3039 P.O. BOX 440 MARYVILLE, MISSOURI 64468-0440